



Model: ST_PTSL07-PM - 7 Industrial Touch Panel mount monitor

- 1.7" 1024x600 resolution, 16:9 aspect ratio
2. Signal input VGA + DVI + HDMI
3. Front IP65 waterproof and dustproof
4. Aluminum alloy case, better performance of heat dissipation
5. True flat 10 Points P-CAP Touch Screen, 5W Resistive Touch 7" industrial level LCD panel, for harsh environment

LCD panel

Panel size	7"
Resolution	High resolution 1024*600
Aspect ratio	16:9
Support Color	16.7M colors
Brightness (cd/m ²)	300 nits
Response time	5ms
Contrast ratio	800:1
View angle	75°/75°/70°/75° (R/L/U/D)

Touch Panel

Touchscreen Type	10 points Capacitive Touch
Touch Interface	USB
Touch Response Time	2ms
Luminousness	90%
Working Life	>50 million times
Touch options	5W resistive touch optional

Signal Ports

VGA	1x VGA
HDMI	1x HDMI
DVI	1x DVI
Audio in/out	1x Audio

OSD

OSD control	Brightness, contrast ratio, auto adjustment, H/V position, language select, etc.
Support Languages	English, French, Spanish, Portuguese, Italian, German, Russian, Japanese, Chinese, etc.
Support OS	Windows XP, Windows 7/8/10, Linux, Mac OS X, Android, ect.

Power Supply

External Power Supply	AC 100 - 240V, 50-60Hz
Working voltage	DC 12V (Wide voltage 12~24V can be optional)
Power consumption	≤48W

Enclosure

Material	Aluminum Alloy
Color	Black, silver for choice
VESA mounting	75x75mm / 100x100mm
IP grade	Front panel IP65 waterproof

Operating Enviroment

Temperature Range	operating: -10 to 60°C, storage: -20 to 80°C
Relative humidity	5%~95% @ 40°C, non condensing
Vibration	5-500 Hz, 0.026 G ² /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Anti-static	Contact 4KV – air 8KV

Packing Details

Net weight	2kg
Gross weight	3kg
Product Dimension	225.4x160.7x59mm
Packing size	400*330*150mm
Accessories	Power adapter, embedded screws

Other

Mounting	wall mounting brackets (optional) desk stand holder (optional)
Warranty	1 year warranty
Certificates	CE, FCC, RoHS

